

The logo for Cambut AG Electronics, featuring the word "CAMBUT" in a bold, sans-serif font inside a yellow stylized shape, with "AG ELECTRONICS" in a smaller font below it.**CAMBUT****AG ELECTRONICS**

GAC™ 2700-LF

Nut Moisture Tester

Get Accurate, Rapid Results Every Time NEW FOR THE NUT INDUSTRY

Discover unparalleled precision in moisture testing with the all-new DICKEY-john GAC™ 2700-LF moisture tester! Our state-of-the-art instrument revolutionizes moisture measurement for raw, processed, or roasted nuts, ensuring precise readings across almonds, pistachios, peanuts, and more nut types. Obtain quick and reliable data critical for maximizing your operation's profitability. The GAC™ 2700-LF unit empowers you to fine-tune your processes, optimize moisture levels, and ultimately elevate your bottom line. Embrace a new era of accuracy and efficiency in nut farming—experience the GAC™ 2700-LF tester difference today.

Features and Benefits:

- Utilizes 149 MHz technology, developed by the USDA
- Measurement results in less than 20 seconds
- Memory storage for up to 5,000 measurements
- Bar code scanner capability to expedite processing time
- Large 7" touch screen display for greater visibility and responsiveness
- Integrated software solution capabilities
- Modern, intuitive operator interface simplifies training and daily operation
- Multiple USB ports on the front and back for software upgrades, USB devices, printer and peripherals
- Advanced instrument security protects the GAC 2700-LF from tampering, adding layers of protection to commercial transactions

**NEW!****DICKEY-john®**
A DIVISION OF TSI®

Cambut AG Electronics

6/139 Sandgate Road
Albion QLD 4010 AUSTRALIA
Phone: +61 7 3391 8766
WhatsApp: +60 17 916 3579
email: apac@cambut.com.au
Web: www.cambut.com.au

www.cambut.com.au

GAC™ 2700-LF

Nut Moisture Tester

Calibrations:

With the rich experience in the industry, DICKEY-john® understands the need to tailor the requirements of your region and operation based on the specific application.

- Best-in-class support backed by DICKEY-john's calibration laboratories
- Convenient, easy-to-download calibrations available on www.dickey-john.com
- Custom calibration development available for unique crop and region attributes

Specifications


Operating Temperature	2 to 45°C
Power	110/220V, 50/60 Hz, 30/35 VA
Humidity	20 to 90% non-condensing
Grain Temperature	-20° to +45°C depending on grain calibrations
Storage/transit Temperature	-20 to +60°C
Moisture Range	5 to 45% (grain dependent)
Approximate Weight	11.43 kg
Approximate Dimensions	43.18cm H x 48.26cm W x 35.56 cm D
Languages	English

Backed by the power of DICKEY-john:

When you buy a DICKEY-john GAC™ 2700-INTL you get all the dependability and value you expect from DICKEY-john® products. Like all DICKEY-john products, the GAC 2700-INTL is designed and manufactured in the USA, and supported worldwide.



Intuitive Color Touchscreen



Multiple Back USB Ports



Change nut types with one touch



Easy-to-Read Results Screen